

# SurLok Plus™ Connectors

## High Reliable in Harsh Environments



SurLok Plus is a field installable and highly reliable alternative to common compression lugs. Due to the IP 67 protection class and a special quick lock and press-to-release design, the SurLok Plus series is suitable for use in harsh environmental conditions.


Energy Storage, E-Mobility, Process Control and Heavy Equipment are the main markets and applications for this connector. Three different colors and different mechanical coding options allow the use of several SurLok connectors side by side without the risk of reverse polarity.

### Main Applications



### Any Questions?

Please feel free to contact us.



### Version: 8.0 mm

Gender	Feature	Color	MPN
Receptacle	Flat busbar	red	<a href="#">SLPRBBPSR</a>
		black	<a href="#">SLPRBBPSB</a>
		orange	<a href="#">SLPRBBPSO</a>
Receptacle	Threaded busbar	red	<a href="#">SLPRBTPSR</a>
		black	<a href="#">SLPRBTPSB</a>
		orange	<a href="#">SLPRBTPSO</a>
Plug/ Right angle	35mm <sup>2</sup> (150 A)	red	<a href="#">SLPPB35BSR</a>
		black	<a href="#">SLPPB35BSB</a>
		orange	<a href="#">SLPPB35BSO</a>
Plug/ Right angle	50mm <sup>2</sup> (200 A)	red	<a href="#">SLPPB50BSR</a>
		black	<a href="#">SLPPB50BSB</a>
		orange	<a href="#">SLPPB50BSO</a>

### Version: 5.7 mm

Gender	Feature	Color	MPN
Receptacle	Flat busbar	red	<a href="#">SLPRABPSR</a>
		black	<a href="#">SLPRABPSB</a>
		orange	<a href="#">SLPRABPSO</a>
Receptacle	Threaded busbar	red	<a href="#">SLPRATPSR</a>
		black	<a href="#">SLPRATPSB</a>
		orange	<a href="#">SLPRATPSO</a>
Plug/ Right angle	16mm <sup>2</sup> (100 A)	red	<a href="#">SLPPA16BSR</a>
		black	<a href="#">SLPPA16BSB</a>
		orange	<a href="#">SLPPA16BSO</a>
Plug/ Right angle	25mm <sup>2</sup> (120 A)	red	<a href="#">SLPPA25BSR</a>
		black	<a href="#">SLPPA25BSB</a>
		orange	<a href="#">SLPPA25BSO</a>

### New Version: 3.6 mm

Current Rating	Gender	Feature	Color	Key	MPN
50A – 70A	Receptacle	Flat busbar	red black	20°	<a href="#">SLPHIRMBPSR1</a> <a href="#">SLPHIRMBPSB1</a>
	Receptacle	Flat busbar	red black	30°	<a href="#">SLPHIRMBPSR2</a> <a href="#">SLPHIRMBPSB2</a>
	Plug/ Right angle	10mm <sup>2</sup> (70 A)	red black	20°	<a href="#">SLPHPM10BSR1</a> <a href="#">SLPHPM10BSB1</a>
	Plug/ Right angle	10mm <sup>2</sup> (70 A)	red black	30°	<a href="#">SLPHPM10BSR2</a> <a href="#">SLPHPM10BSB2</a>

### Version: 10.3 mm – On Request

### Quick and Easy

Our E-Commerce Platform offers you a comprehensive portfolio of Connector types with one click or scan of the QR code.

